

Specification - Sunex One Rectangular

Revision 1



Product Information		
Model No.	RC20LED	RC40LED
Power Consumption(±5%)	20w	40w
Power Supply	Philips or European Brand	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	COB	
Beam Angle	80 degrees	
Luminous Flux (±10%) 3000k Ra80	2150lm	4300lm
Luminous Flux (±10%) 4000k Ra80	2340lm	4685lm
Efficiency (4000k)	>115lm per watt	
CCT	3000k , 4000k , 5000k (6000k special order)	
Colour Rendering Index	Ra80	
Class	Class I	
SCDM	< 3	
Diffuser Type	Frosted Glass	
IP Rating	IP20	
Colour	White	
Dimensions (LxWxH)	240x150x90mm	240x150x90mm
Cut Out	230x140mm	230x140mm
Options		
Dimmable	Dali, 1-10v or Triac	
Emergency	Standard, self test, Dali self test	
Sensor	Remote	

Applications

Board Rooms, Corridors, Hotels, Reception Area's, Retail

Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20
Warranty	5 years