

Specification - Com Lite CP Models (Opal Diffuser)

Revision 1



Product Information						
Model No.	CP220	CP20	CP40	CP30	CP55	CP65
Power Consumption(±5%)	20w	20w	40w	24w	48w	65w
Power Supply	Lifud					
Input Voltage	220-240 VAC, 50-60Hz					
Power Factor	>0.90					
Driver Type	Constant Current					
LED Type	SMD					
Luminous Flux (±10%) 4000k	2100lm	2100lm	4100lm	3050lm	6120lm	8500lm
Luminous Flux (±10%) 5000k	2000lm	2000lm	4000lm	3000lm	6100lm	8980lm
Efficiency	>100lm per watt	>100lm per watt	>100lm per watt	> 125lm per watt	> 125lm per watt	> 125lm per watt
CCT	4000k or 5000k					
Color Rendering Index	Ra80					
Beam Angle	120 degrees					
Class	Class I					
SCDM	< 6					
IK rating	IK08					
IP Rating	IP65					
Clips	304 stainless steel x 12pcs					
Dimensions (mm)	600x100x73	1200x100x73	1200x100x73	1500x100x73	1500x100x73	1500x100x73
Options						
Dimmable	Dali, DSI, 1-10v, Triac					
Emergency	Standard, self test, Dali self test					
Sensors	Inbuilt microwave , batten mount PIR					
Applications						
Farmyards, Garages, Plantrooms, Underground car parks, Workshops , Warehouses						
Lifespan and Warranty						
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20					
Warranty	5 years					