

Specification - Com Lite Suspended Linear Direct/Indirect low UGR

Revision 1



Product Information		
Model No.	TSDIDLG38	TSDIDLG50
Power Consumption(±5%)	38w	50w
Power Supply	Boke/Lifud	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	SMD led	
UGR	<19	
Luminous Flux (±10%) 4000k Ra80	4380lm	5460lm
Efficiency (4000k)	> 110lm per watt	
CCT	3cct 3000/4000/5000k	
Colour Rendering Index	Ra80	
Beam Angle	90 degrees (75% downlight, 25% uplight)	
Class	Class I	
SCDM	< 6	
IK rating	IK06	
IP Rating	IP20	
Colour	Black , Grey or White	
Dimensions (LxWxH)	1274x228x37mm 1574x228x37mm	
Options		
Dimmable	Dali, DSI, 1-10v	
Emergency	Standard, self test, Dali self test	
Sensor	Remote option only	
Applications		
Board Rooms, Corridors, Offices, Reception Area's		
Lifespan and Warranty		
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20	
Warranty	5 years	