



Specification - Com Lite Multi-watt 3CCT Model

Revision 1



Product Information

Model No.	ECPMW
Power Consumption(±5%)	30w, 50w
Power Supply	Tridonic
Input Voltage	220-240 VAC, 50-60Hz
Power Factor	>0.90
Driver Type	Constant Current
LED Type	SMD
Luminous Flux (±10%) 4000k 30w	3930lm
Luminous Flux (±10%) 4000k 50w	6550lm
Efficiency	> 130lm per watt for 4000k
CCT	3000k, 4000k, 6000k
Color Rendering Index	Ra80
Beam Angle	120 degrees
Class	Class I
SCDM	< 6
IK rating	IK08
IP Rating	IP65
Clips	304 stainless steel x 12pcs
Body Material	ABS Base, Polycarbonate Diffuser
Dimensions	1520x85x80mm

Options

Dimmable	Dali, DSI, 1-10v, Triac
Emergency	Standard, self test, Dali self test
Sensors	Inbuilt microwave , batten mount PIR



Applications

Farmyards, Garages, Plantrooms, Underground car parks, Workshops, Warehouses

Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20				
---------------------------	-----------------------	--	--	--	--

Warranty	5 years				
----------	---------	--	--	--	--