

## Specification - Com Lite tubular IP66



Product Information		
Model No.	CTL40W	CTL50W
Power Consumption(±5%)	40w	50w
Power Supply	Philips, Osram, Lifud or Boke	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	SMD	
Luminous Flux (±10%) 4000k	5920lm	7360lm
Efficiency	> 145lm per watt	
CCT	4000k , others on special request	
Colour Rendering Index	Ra80	
Surge Protection	1kv line -line, 2kv line -Earth	
Beam Angle	120 degrees	
Class	Class II	
SCDM	< 6	
IK rating	IK10	
IP Rating	IP66 - IP69K for harsh environments	
Clips	Stainless steel 304	
Dimensions	1128x120x84mm	1390x120x84mm
Options		
Dimmable	Dali, DSI, 1-10v	
Emergency	Standard, self test, Dali self test	
Sensors	Batten mount PIR or microwave	
Applications		

Exterior walls, Farmyards, Garages, Plantrooms, Underground car parks, Workshops , Warehouses

### Accessories

CTL/SUSKIT Suspension kit (not supplied, needs to be ordered separately)

Lifespan and Warranty	
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20
Warranty	5 years