

Specification - Com Lite wallpack WP Model

Revision 1



Product Information		
Model No.	WP30MC	WP50MC
Power Consumption(±5%)	27w	49w
Power Supply	Boke	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	SMD led	
Luminous Flux (±10%) 4000k Ra80	3240lm	5880lm
Beam Angle	120 degrees	
Material		
Material	Aluminium Alloy and Polycarbonate lens	
Efficiency (4000k)	> 115lm per watt	
CCT	Selectable 3000/4000/6000k	
Colour Rendering Index	Ra80	
Operating Temperature	-20 to 40 degrees	
Class	Class I	
SCDM	< 6	
IK rating	IK08	
IP Rating	IP65	
Colour	Black	
Dimensions	309x275x117mm	
Options		
Dimmable	Dali, DSI, 1-10v	
Emergency	Standard, self test, Dali self test	
Sensor	Inbuilt microwave and/or photocell	
Applications		
Carehomes, Hospitals, Stairwells, Public Buildings and schools		
Lifespan and Warranty		
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20	
Warranty	5 years	